
NASA TECH BRIEF



NASA Tech Briefs are issued by the Technology Utilization Division to summarize specific technical innovations derived from the space program. Copies are available to the public from the Clearinghouse for Federal Scientific and Technical Information, Springfield, Virginia, 22151.

Superconductor Shields Test Chamber From Ambient Magnetic Fields



The problem: Constructing an inexpensive test chamber that maintains a constant, low magnetic field.

The solution: A test chamber that is shielded from ambient magnetic fields by a lead foil cylinder maintained in a superconducting state by liquid helium.

How it's done: The lead cylinder, constructed of 0.007-inch-thick foil, is suspended in a Dewar vessel filled with liquid helium to cool the lead to a superconducting state. A current is induced in the lead foil cylinder by the application of a very small magnetic

field (less than 2×10^{-5} gauss) during the cooling process. The central space within this Dewar system then encloses the initially applied small magnetic field at a constant value even in the presence of steady or changing ambient magnetic fields.

Notes:

- The internal field of this device has been demonstrated to be axially stable to better than +1 gamma (10⁻⁵ gauss) -2 gamma in an ambient field of 500 gamma.
- This innovation should be useful as a laboratory research and testing device for magnetic components.

(continued overleaf)

This document was prepared under the sponsorship of the National Aeronautics and Space Administration. Neither the United States Government nor any person acting on behalf of the United States

Government assumes any liability resulting from the use of the information contained in this document, or warrants that such use will be free from privately owned rights.

3. Inquiries concerning this innovation may be directed to:

Technology Utilization Officer Jet Propulsion Laboratory 4800 Oak Grove Drive Pasadena, California, 91103 Reference: B65-10297 Patent status: NASA encourages commercial use of this innovation. No patent action is contemplated by NASA.

Source: A. F. Hildebrandt

(JPL-627)